


Raccords instantanés LF 3800 / Raccords d'implantation

3800 Cartouche monobloc

Acier inox 316L, FKM




ØD		G	G1	H	H1	H2	N	Kg
4	3800 04 00	9,8	8	17	8,5	8,5	11	0,006
6	3800 06 00	12,1	10	19	10,5	8,5	13,5	0,008
8	3800 08 00	14,8	13	21	12,5	8,5	16	0,012
10	3800 10 00	17,5	15	24,5	14	10,5	20	0,019

Les dimensions des cavités sont disponibles sur demande

3809 Équerre, mâle BSPT

Acier inox 316L, FKM




ØD	C		F	G	H	L	Kg
4	R1/8	3809 04 10	10	10	23,5	16,5	0,020
6	R1/8	3809 06 10	13	12	27,5	20	0,030
	R1/4	3809 06 13	14	12	27,5	25	0,036
8	R1/8	3809 08 10	14	15	32	25	0,040
	R1/4	3809 08 13	14	14,5	34	25	0,045
10	R1/4	3809 10 13	19	17,5	37,5	27,5	0,068
	R3/8	3809 10 17	19	17,5	37,5	27,5	0,069

Raccord orientable

3809 Équerre, mâle NPT

Acier inox 316L, FKM




ØD	C		F	G	H	L	Kg
6	NPT1/8	3809 06 11	13	12,5	29	22,5	0,031
	NPT1/4	3809 06 14	14	12,5	29	22,5	0,036
8	NPT1/8	3809 08 11	14	15	34	24	0,040
	NPT1/4	3809 08 14	14	15	34	24	0,045
10	NPT1/4	3809 10 14	19	17,5	39,5	30	0,068
	NPT3/8	3809 10 18	19	17,5	39,5	30	0,071

Raccord orientable

3899 Équerre, mâle BSPP et métrique

Acier inox 316L, FKM




ØD	C		F	G	H	L	Kg
	M5x0,8	3899 04 19	10	10	26	18	0,020
4	G1/8	3899 04 10	13	10	27	19	0,022
	G1/4	3899 04 13	17	10	27	19	0,018
	M5x0,8	3899 06 19	13	12	33	24	0,031
6	G1/8	3899 06 10	6	12	33	24	0,031
	G1/4	3899 06 13	17	12	32	24	0,036
	G1/8	3899 08 10	14	15	35	25	0,039
8	G1/4	3899 08 13	17	15	35	25	0,044
	G3/8	3899 08 17	21	15	34,5	25	0,048
	G1/4	3899 10 13	19	17	43	31	0,069
10	G3/8	3899 10 17	21	17	42	31	0,072

Raccord orientable

3889 Équerre compacte, mâle BSPT

Acier inox 316L, FKM




ØD	C		F	G	H	L	Kg
4	R1/8	3889 04 10	13	10	18	17	0,019
	R1/4	3889 04 13	17	10	19,5	16,5	0,018
6	R1/8	3889 06 10	13	12	21,5	20,5	0,025
	R1/4	3889 06 13	14	12	21,5	20,5	0,032
8	R1/8	3889 08 10	14	15	24	22	0,036
	R1/4	3889 08 13	14	15	24	22	0,036
10	R1/4	3889 10 13	17	17,5	28,5	27,5	0,058
	R3/8	3889 10 17	19	17,5	28,5	27,5	0,068
	R1/4	3889 12 13	22	20	33,5	30	0,088
12	R3/8	3889 12 17	22	20	33,5	30	0,090
	R1/2	3889 12 21	22	20	33,5	33	0,097

Raccord orientable. Max. 20 bar

3889 Équerre compacte, mâle NPT

Acier inox 316L, FKM



ØD	C		F	G	H	L	Kg
4	NPT1/8	3889 04 11	13	10	17,5	19	0,019
	NPT1/8	3889 06 11	13	12,5	20	22,5	0,026
6	NPT1/4	3889 06 14	14	12,5	20	22,5	0,033
	NPT1/8	3889 08 11	13	15	25	24	0,036
	NPT1/4	3889 08 14	14	15	24	24	0,036
8	NPT1/4	3889 10 14	17	17,5	27,5	27,5	0,059
	NPT3/8	3889 10 18	19	17,5	28,5	26,5	0,068
10	NPT1/4	3889 12 14	22	20	31,5	32,5	0,086
	NPT3/8	3889 12 18	22	20	32,5	32,5	0,089
12	NPT1/2	3889 12 22	22	20	27,5	32,5	0,098

Raccord orientable. Max. 20 bar