



PRODUCT-DETAILS

TY400-40X-100

CBL TIE 40LB 15IN UV BLACK NYLON



General Information

Extended Product Type	TY400-40X-100
Product ID	7TAG054360R0314
EAN	5414363064596
Catalog Description	CBL TIE 40LB 15IN UV BLACK NYLON
Long Description	Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to 105 Degrees Celsius, Weather and Ultraviolet Resistant for Indoor and Outdoor Applications, UL/IEC 62275 Type 2/21S Rated for AH-2 Plenum and as a Flexible Cable and Conduit Support, Length of 370mm, Width of 3.6mm, Thickness of 1.2mm , Tensile Strength Rating of 180 Newtons, 100 Pack

Ordering

EAN	5414363064596
UPC	786210713212
Country of Origin	Hungary (HU) United States (US)
Selling Unit of Measure	each

Dimensions

Product Net Width	3.6mm 0.142 in
Product Net Depth / Length	370 mm 14.567 in

Container Information

Package Level 1 Units	100 piece
Package Level 1 Width	1 in 25 mm
Package Level 1 Height	6 in 152 mm
Package Level 1 Depth / Length	18 in 457 mm
Package Level 2 Units	500 piece
Package Level 2 Width	5 in 127 mm
Package Level 2 Height	15 in 381 mm
Package Level 2 Depth / Length	5 in 127 mm

Environmental

REACH Information	False - does not contain substances > 0.1 mass percentage
-------------------	---

Technical UL/CSA

Flammability According to UL94	V-2
--------------------------------	-----

Additional Information

Brand / Label	Ty-Fast
Bundle Diameter	6.35 to 102 mm 0.25 to 4.016 in
Color	Black
Effective Date	19970602
Lock Type	Plastic Pawl
Material	Nylon/Polyamide 6.6
Product Main Type	CABLE TIES AND ACCESSORIES
Product Name	Plastic cable tie
Product Type	General Purpose
Special Functions	The integrally formed polyamide pawl combines low insertion and high locking strength. The low profile head significantly reduces the potential for snagging during installation. Quick and easy pull through increases productivity, reduces operator fatigue. Tail with finger grip design that helps operator grasp and pull ties snugly. Sure grip tab keeps the tail from popping out while being treated, then holds it it securely for final tightening by hand or tool
Standards	UL E49405
Temperature Range	-40 to 105 °C -40 to 221 °F
Tensile Strength	180 N

	40 lb
Thickness	1.2 mm 0.047 in

Certificates and Declarations

Data Sheet, Technical Information	TDS000751
Declaration of Conformity - CE	9AKK107492A9843

External Classifications and Standards

ETIM 7	EC000046 - Cable tie
ETIM 8	EC000046 - Cable tie
ETIM 9	EC000046 - Cable tie
UNSPSC	39121703
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5034 >> Cable ties

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Cable Ties

