

SMS

SMS 1145

MATERIAL MATIÈRE MATERIAL

SS = Stainless steel Inox


SIZE DIMENSIONS DIMENSIONES

From DN 25 to 100 mm

THREAD FILETAGE ROSCA


SMS 681

MALE PART NEZ FILETÉ



DN	F	d
25	1"	40x1/6"
38	1 1/2"	60x1/6"
51	2"	70x1/6"
63	2 1/2"	85x1/6"
76	3"	98x1/6"
104	4"	125x1/4"

FEMALE PART PIÈCE LISSE



A	d
35,5	22,5
55	35,5
65	48,5
80	60,5
93	72,9
118	100

NUT ECROU



F	A	B	L
40x1/6"	51	32,5	19
60x1/6"	74	48,5	23
70x1/6"	84	61	24
85x1/6"	100	74	28
98x1/6"	114	87	30
125x1/4"	138	113	31

GASKET JOINT DE RACCORD



A	B	C
32	25	22,5
48	38	35,5
61	51	48,5
73,5	63,5	60,5
86	76	72,9
116	104	100

6 encoches
Attention : Ø100 , identifier ØB

SMS	ØA	ØB
25	35,5	40 6F"
32	43	48 6F"
38	55	60 6F"
51	65	70 6F"
63	80	85 6F"
76	93	98 6F"
104	118	125 4 F"
101,6	118	132 6F"

AL = Aluminium BR = Brass Laiton Latón ST = Steel Acier Acero SS = Stainless steel Inox PP = Polypropylene

Trelleborg Fittings 2018

		DN coupling Diam. raccord Diam. racor	DN shank Diam. douille Diam. espiga	Ref.	Notes
 <p>Female. Serrated hose shank. For circlip. Femelle. Douille crantée. Pour jonc. <i>Hembra. Caña acanalada. Para anillo.</i></p>	<p>PAGE 99. Circlip and ferrule. Jupe et jonc. <i>Junta y anillo.</i></p>	SS 316L	25	25	0116983
			32	32	5100286
			38	38	0116917
			51	51	0116919
			63	63	0116863
			76	63	0117871
			76	76	0116921
			104	101,5	0116923
 <p>Male. Serrated hose shank. For circlip. Mâle. Douille crantée. Pour jonc. <i>Macho. Caña acanalada. Para anillo.</i></p>	<p>PAGE 99. Circlip and ferrule. Jupe et jonc. <i>Junta y anillo.</i></p>	SS 316L	25	25	0116984
			32	32	5100285
			38	38	0116916
			51	51	0116918
			63	63	0116864
			76	76	0116920
			104	101,5	0116922
			 <p>Nut. Ecrou. Tuerca.</p>		SS 304
32		5100284			
38		0116872			
51		0116862			
63		0116865			
76		0116868			
104		0116874			
 <p>Rubber coated nut. Ecrou surmoulé caoutchouc. Tuerca engomada.</p>		SS 304	25		5101012
			38		5100792
			51		5100749
			63		5100786
			76		5100787
 <p>Gasket. For male SMS. Joint. Pour mâle SMS. Junta. Para macho SMS.</p>		EPDM	25		5100582
			38		5100583
			51		5100584
			63		5100585
			76		5100586
			104		5100587

AL = Aluminium BR = Brass Laiton Latón ST = Steel Acier Acero SS = Stainless steel Inox PP = Polypropylene

Trelleborg Fittings 2018

		DN coupling Diam. raccord Diam. racor	DN shank Diam. douille Diam. espiga	Ref.	Notes	
	Spanner. Clé de serrage. <i>Llave de presión.</i>	SS 304		5101543		
	Female. Serrated hose shank. With collar. Femelle. Douille crantée. A collerette. <i>Hembra. Caña acanalada. Con cuello.</i>	SS 316L	25	25	5101829	 page 162
			38	38	5101813	
			51	51	5101831	
			63	63	5101832	
			76	76	5101833	
			104	101,5	5102029	
	Male. Serrated hose shank. With collar. Mâle. Douille crantée. A collerette. <i>Macho. Caña acanalada. Con cuello.</i>	SS 316L	25	25	5101834	 page 162
			38	38	5101835	
			51	51	5101836	
			63	63	5101837	
			76	76	5101838	
			104	101,5	5102293	
	Female. Smooth shank. With collar. Femelle. Douille lisse. A collerette. <i>Hembra. Caña lisa. Con cuello.</i>	SS 316L	25	25	5005004	 page 162
			38	38	5005006	
			51	50,5	5005008	
			63	63	5101848	
	Male. Smooth shank. With collar. Mâle. Douille lisse. A collerette. <i>Macho. Caña lisa. Con cuello.</i>	SS 316L	25	25	5005003	 page 162
			38	38	5005005	
			51	50,5	5005007	
			63	63	5101849	
	Female for welding. Femelle à souder. <i>Hembra para soldar.</i>	SS 316L	25	25	5100572	
			38	38	5100529	
			51	51	5100527	
			63	63,5	5100573	
			76	76,1	5100574	
			104	104	5100575	
	Male for welding. Mâle à souder. <i>Macho para soldar.</i>	SS 316L	25	25	5100576	
			38	38	5100577	
			51	51	5100578	
			63	63,5	5100579	
			76	76,1	5100580	
			104	104	5100581	