



Raccordi a saldare e filettati in acciaio al carbonio







CARBON STEEL WELDING AND THREADED FITTINGS


SCHWEISS-UND GEWINDEFITTTINGE AUS STAHL

RACCORDS EN ACIER FILETÉS ET À SOUDER

RACORES A SOLDAR Y ROSCAR EN ACERO AL CARBONO

Certificazioni / Certifications

		QUALITY ASSURANCE SYSTEM IN ACCORDANCE WITH PRESSURE EQUIPMENT DIRECTIVE 2014/68/EU	DGR-0036-QS-W 192/2003/MUC-001
		RACCORDERIE METALLICHE S.P.A. ÁLTAL GYÁRTOTT ACÉL HEGESZTHETŐ IDOMOK, CSÓÍVEK, MENETES VÉGEK	A-43/2017
		CARBON STEEL WELD FITTINGS	POCC IT.AM05.H05079






268/Z


MANICOTTO ZINCATO

- GALVANIZED SOCKET
- MUFFE G. L. VERZINKT
- MANCHON GALVANISÉ
- MANGUITO GALVANIZADO

TYPE: International Nr. 16
MATERIAL: P235TR1 - S235 (R.St.37.0)
NORM: UNI / DIN EN 10241 (ex DIN 2986)
THREAD: EN 10226-1 (ex ISO 7/1)

R 10 11

CODE	DN	DN inch	D2 mm	L min mm				€
268108001	6	1/8"	14	17	12	200	-	1,48
268104001	8	1/4"	18,5	25	23	200	-	1,31
268308001	10	3/8"	21,3	26	33	150	-	1,31
268102001	15	1/2"	26,4	34	63	150	14400	1,48
268304001	20	3/4"	31,8	36	80	150	8400	1,93
268100001	25	1"	39,5	43	142	100	5600	2,88
268114001	32	1"1/4	48,3	48	189	50	2800	4,53
268112001	40	1"1/2	54,5	48	220	40	2240	5,59
268200001	50	2"	66,3	56	320	25	1400	7,70
268212001	65	2"1/2	82	65	530	6	-	12,08
268300001	80	3"	95	71	680	6	-	17,08
268400001	100	4"	122	83	1100	6	-	33,38
268500001	125	5"	147	92	1531	4	-	82,96
268600001	150	6"	174	92	2212	2	-	152,24



704

CURVA DIMA 3D 90° DA TUBO SENZA SALDATURA

- SEAMLESS ELBOW 3D 90°
- NAHTLOSE ROHRBÜGEN BA3 90°
- COURBE 3D 90° DE TUBE SANS SOUDURE
- CODO PARA SOLDAR 3D 90° (DE TUBO SIN SOLDATURA)

MATERIAL: P235TR2 - S235 (R.St.37.0)

NORM: EN 10253-1 (DIN 2605)

CODE	DN	DN inch	DN mm	S mm	R mm	B mm				€
704172000*	10	3/8"	17,2	2	19	28	0,04	100	-	9,66
704213000	15	1/2"	21,3	2	29	38	0,04	100	9600	4,89
704269000	20	3/4"	26,9	2,3	29	43	0,06	100	9600	4,89
704337000	25	1"	33,7	2,6	38	56	0,11	80	4480	3,88
704424000	32	1 1/4"	42,4	2,6	48	70	0,19	100	3600	4,92
704483000	40	1 1/2"	48,3	2,6	57	83	0,26	50	1800	5,96
704570000	-	-	57	2,9	72	100	0,44	25	900	13,42
704603000	50	2"	60,3	2,9	76	106	0,49	25	900	9,65
704700000	-	-	70	2,9	92	127	0,7	10	720	16,56
704761000	65	2 1/2"	76,1	2,9	95	132	0,78	5	660	15,46
704889000	80	3"	88,9	3,2	114	159	1,22	5	350	22,60
704101000	-	3 1/2"	101,6	3,6	133	184	1,82	4	192	31,72
704108000	-	-	108	3,6	142,5	196	2,07	4	192	39,19
704114000	100	4"	114,3	3,6	152	210	2,35	4	192	42,95
704133000	-	-	133	4	181	247	3,62	1	90	70,81
704139000	125	5"	139,7	4	190	262	4	1	84	72,00
704159000	-	-	159	4,5	216	295	5,82	1	60	110,53
704168000	150	6"	168,3	4,5	229	313	6,52	1	60	116,50
704193000	175	-	193,7	5,6	270	367	11,02	1	24	222,00
704219000	200	8"	219,1	6,3	305	414	15,96	1	24	297,37
704244000	-	-	244,5	6,3	340	462	19,77	1	12	596,00
704273000	250	10"	273	6,3	381	518	24,8	1	9	636,54
704323000	300	12"	323,9	7,1	457	619	39,82	1	9	954,31
704355000	350	14"	355,6	8	533	711	57,47	1	-	on demand
704406000	400	16"	406	8,8	610	813	82,6	1	-	on demand
704508000*	500	20"	508	11	762	1016	161	1	-	on demand
704609000*	600	24"	609	12,5	914	1219	271,38	1	-	on demand

Tolleranze dimensionali / Dimensional tolerances

$D = \pm 1\% D \text{ MIN } \pm 0,5 \text{ mm}$

$S = S \leq 4 \text{ mm } [-12,5\% \times S / +20\% \times S] S > 4 \text{ mm } [-12,5\% \times S / +15\% \times S]$

$R = \pm 2 \text{ mm } \leq \text{DN } 200 \pm 3 \text{ mm } > \text{DN } 200 \leq \text{DN } 400 \pm 14,5 \text{ mm } \text{DN } 500 - 600$

$B = \pm 7 \text{ mm } \leq \text{DN } 400 \pm 6 \text{ mm } \text{DN } 500 - 600$

[*] Dimensioni non previste nella norma EN 10253-1 - Sizes not provided in EN 10253-1