



QMFZ2.E111943 Plastics - Component

[Page Bottom](#)

[Questions?](#)

[Previous Page](#)

Plastics - Component

Guide Information

DOW CORNING KOREA LTD
 690-1 GWANGHYEWON-RI
 JINCHON-GUN, GWANGHYEWON-MYON
 365-830
 CHOONGCHONGBUK-DO, KOREA

E111943

Material Dsg	Color	Min. Thk mm	Flame Class	H		RTI		H	D	C
				W	A	Elec	Mech	V	4	
				I	I	Imp	Str	T	9	
Silicone "Room Temperature Vulcanizing" (RTV), sealant/adhesive, furnished as paste.										
LDC, CF 2101										
	WT, TL	2.3	HB	-	-	105	105	105		
Silicone "Room Temperature Vulcanizing" (RTV), furnished as TUBE OR CARTRIDGE.										
CN8603	NC	2.0-2.2	V-0	-	-	105	105	105		
Silicone (SI), furnished as paste.										
SE9590	NC	1.5 ONLY	V-0	-	-	105	105	105		
Silicone Molding Resin (SIR), sealant, "Solar", furnished as one liquid component.										
PV 804	BK	1.9	HB	-	-	150	150	150		
Silicone Molding Resin (SIR), sealant, furnished as one liquid component.										
CF-1100	WT	1.0 ONLY	HB	-	-	150	150	150		
Dow Corning 732										

	WT	0.87 ONLY	HB	-	-	150	150	150			
Dow Corning 780											
	WT	0.63	HB	-	-	150	150	150			
	GY	1.2	HB	-	-	150	150	150			
LDC-7091, DC-7091											
	GY	0.73	HB	-	-	150	150	150			
	WT	2.0	HB	-	-	150	150	150			
LDC-737, DC-737											
	CL	0.67	HB	-	-	150	150	150			
	WT	0.69	HB	-	-	150	150	150			
Silicone Molding Resin (SIR), w/ pigment part B, furnished as uncured w/ vulcanizing agent LS-5.											
FM-360U	BK	0.75 ONLY	V-0	0	0	150	150	150	0	5	1
Silicone Molding Resin (SIR), furnished as one liquid component.											
8888	RD	1.7 ONLY	HB	-	-	150	150	150			
K730	NC	1.0	HB	-	-	150	150	150			
		2.3	HB	-	-	150	150	150			
K740	NC	1.0	HB	-	-	150	150	150			
		2.4	HB	-	-	150	150	150			
K750	NC	0.99	HB	-	-	150	150	150			
		2.5	HB	-	-	150	150	150			
K760	NC	1.2	HB	-	-	150	150	150			
		2.6	IIB	-	-	150	150	150			
K761	NC	1.1	HB	-	-	150	150	150			
		2.4	HB	-	-	150	150	150			
K770	NC	1.1	HB	-	-	150	150	150			
		2.5	HB	-	-	150	150	150			
K780	NC	1.1	HB	-	-	150	150	150			
		2.7	HB	-	-	150	150	150			
Silicone Molding Resin (SIR), furnished as uncured w/ vulcanizing agent LS-3.											
FM-351U	DK, GY	0.41 ONLY	V-0	-	-	150	150	150			

Silicone Molding Resin (SIR), furnished as uncured w/ vulcanizing agent LS-5.										
CF508U	NC	0.96	HB	-	-	150	150	150		
		2.0	HB	-	-	150	150	150		
FM-350U	GY	0.38 ONLY	V-0	1	0	150	150	150	0	3 0

Marking: Company name and material designation on container, wrapper or finished part.

Page Top	Notice of Disclaimer	Questions?	Previous Page
UL Listed and Classified Products	UL Recognized Components	Products Certified for Canada	

This page and all contents are Copyright © 2004 by Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2004 Underwriters Laboratories Inc.®"